



Ideal for any business on the move !



The new standard for mobile printers



Compact, lightweight design allows for comfortable use. It does not get in the way of work when you wear it on your waist or shoulder.

Labels are issued with Bluetooth-compatible wireless communications. Work efficiently without troublesome cables.

peedy High-speed printing of up to 100 mm per second. Work quickly with faster printing.

The compact body is loaded with convenient functions.

View operations on the LCD.

Issue large amount of labels with the DP-2L printer.

Settings and operations are displayed on user-friendly menus. Errors such as improperly loaded labels are also displayed, making it easy for anyone to master operations.

The "L" type supports desk-top

standard 18-meter label rolls as well

that require larger amounts of labels

* Available as an option at time of delivery

as mobile standard 10-meter label

rolls. Easily supports operations

to be issued.

Small



Supports both Tear-Off and Peel-Off modes.

Labels can be issued either in Tear-Off or Peel-Off mode. All the features necessary for a label printer have been condensed into a compact size.

Equipped with a high performance and high durability battery.

Large capacity lithium ion battery allows for long operation time. Excellent performance can be kept for a long period even after repeated recharging.



Compatible with various makes of hand-held data terminals.

Compatible with any Bluetoothenabled hand-held data terminal. Your existing equipment can be used effectively and easily.



Heavy-duty design provides peace of mind.

Choose optional accessories that best suit your needs, including a protector that prevents damage to the main body even when dropped from a height of 120 cm, a convenient belt hook for carrying, a portable holster, and an auxiliary case.

* When using the protector and belt hook

Daily business and service will change.

SEI MART

228 \$2.00

0210 2504

078 LETTUCE

Issue product

labels anywhere.





Portability makes in-store labeling easy.



Inventory control labels



06102000099

Work comfortably in warehouses.



or door-to-door sales.







Display Pass Consumable goods Print head replaced Cleaning Finished

SHINSEI SERVICE

Issue on-site tracking labels for equipment inspection or asset management.

Mobile Printer DP-2







00018356 Taro Shinse 2007.3.20 AK15-135 ower supply Pass ver Pass inter Pass



Options



Battery charger (CH-74)



Charger adapter (CV-74)



Lithium-ion battery (BH-74)



Protector (DP-74) * DP-74L for "L" type



Interface cable (C-74)

Belt hook

(DH-74B)



Media roll

M

Portable holster

(DH-74)



Auxiliary case (HH-74)

Product Specifications

Specifications / Model name		Mobile Printer DP-2	Mobile Printer DP-2L	
Printer unit	Print method	Direct thermal		
	Print resolution	8 dots / mm (203 dpi)		
	Print speed	Max. 100mm/second (at standard printing)		
	Max. print area	48mm (W) x 100mm (L)(standard specification)		
Dimensions		123mm (L) x 85mm (W) x 64mm (H) (excluding protruding pa	ts) 146mm (L) x 85mm (W) x 76mm (H) (excluding protruding parts)	
Weight		398g (including battery)	411g (including battery)	
Power supply	Battery	Exclusive lithium ion battery (7.4V 2500mAh)		
Display unit	LCD	128 x 64 dot matrix LCD (with backlight)		
	LED	3 LEDs (Power, Status, Charge)		
Operating panel	Buttons	3 buttons (Power, Menu, Feed)		
Interface	Bluetooth	Conforming to Bluetooth Ver. 1.2 (Class 2)		
	RS232C	Dedicated cable		
Command language		SPLM (command method using dedicated protocols)		
Print mode		Tear-Off, Peel-Off		
Labels (Outside wound)	Backing paper width	24 - 58mm		
	Label external diameter	Max. 58mm (mobile standard labels)	Max. 70mm (desk-top standard labels)	
	Label type	I mark/Black mark, Gap, Journal		
Font .		Outline fonts (scalable): A Gothic, F Eu Pop font	SSF1: 16x24 dots SSF2: 24x32 dots A Gothic, F European, C European, Gothic B, MINCHO L, OCR-B	
		Bit map Kanji fonts (JIS Level 1 & 2): Gothic: 16x16 MINCHO: 22x Outline Kanji fonts (JIS Level 1 & 2) : Gothic (Scala	MINCHO: 22x22, 24x24 dots	
Barcode type		EAN 8, EAN 13, JAN 8, JAN 13, UPC-A, UPC-E, NW-7, Interleaved 2 of 5 (ITF), CODE 39, CODE 128, EAN 128, RSS		
Two-dimensional code		QR Code, PDF417		
Regulatory approvals		FCC Class A, CE, IC		
Functions	Self-diagnosis	Error message is displayed on the LCD.		
	Power saving	Sleep mode, Auto power off, Remaining battery level indication		
Optional accessories		Charger adapter, Extra battery pack, Rainproof case, Data transfer cable		

* Design and specifications are subject to change without notice.



Shinsei Industries Co., Ltd

Headquarters 4-12-15 Horifune, Kita-ku, Tokyo 114-0004 TEL: 81-3-3913-0395 FAX: 81-3-3913-9607 http://www.shinseiind.co.jp/