

## JP-600

JP-600 is a portable barcode printer designed for ease of use based on each customer's requirement. Anyone can operate it easily, and it has an easy function guide to notify the user by displaying the message when an incorrect data was entered. It is also equipped with self-check function, which gives an alarm to the user in case of trouble.



### ■ Common Features

- Both AC and DC power sources
- Both Direct Thermal and Thermal Transfer configurations
- Presetting data up to 2,000 items
- EAN and UPC barcode printable
- Pen scanner terminal available

### ■ Options

- Imprints on transparent films or labels
- ITF, CODE39, CODE128 barcodes are available.
- Markdown function
- Online printing function to directly issue labels from Microsoft Excel
- Enables the user to draw up a whole data sheet of labels.

Application software "Label Editor" for Windows is required.



### ■ Specifications

#### ■ Main Body

- |                       |  |
|-----------------------|--|
| • Printing System     | Direct thermal / Thermal transfer                      |
| • Printing Resolution | 8 dots/mm (200dpi) Maximum printing width 56mm         |
| • Printing Speed      | 50mm/sec or more (40mm/sec or more in case of thermal) |

	transfer)
• Memory	Embedded in the body ROM 1MB      RAM128KB
• Display Mode	Liquid-crystal Dot Matrix 16 letters × 2 lines
• Fonts	Numerals, alphabets, symbols
• Barcode Symbologies	EAN, UPC, JAN      (NW7, ITF, CODE39, CODE128 are available at the user's option. )
• Input Mode	Manual key-board 26 keys, External input (interactive mode)
• Interface	RS-232C (9 pins) , Scanner Connector
• Transmission Speed	Standard 9600bps maximum 38400bps
• Weight	1.5Kg (not including label and battery)
• Dimension	W 168mm × D 229mm × H 113mm
• Clock Function	Equipped as standard
• Other Functions	Peel-off printing、 Display of the remaining battery capacity, Automatic adjustment of print density, Automatic setting of printing system
• Environment	Operating temperature 5°C~35°C Humidity 25%~60%(Non condensation)
<b>■Power Source</b>	
• Battery Pack	Dimension : W 36mm × D 220mm × H 86mm Weight:500g
• Charging Time	3~4hours (when charged by battery charger CH-02V/03V)
• Battery Capacity	Approx. 5,000~7,000 labels on a full charge (depending on the printing content, label size)
• AC/DC Adapter	Dimension: W 66mm × D 220mm × H 86mm Weight:600g Output: DC12V, Input: Input AC85~132V
<b>■Label</b>	
• Material	Thermal Paper (bond paper, synthetic paper) : Direct imprinting Standard Paper (bond paper, synthetic paper) : Thermal transfer imprinting
• Size	W24mm×L16.8mm, 17.8mm, 21.6mm, 25.2mm, 27.5mm W32mm×L16.8mm, 17.8mm, 21.6mm, 25.2mm, 27.5mm, 37.8mm W40mm×L27.5mm, 43.0mm, 60.0mm, 75.6mm W56mm×L17.8mm, 25.2mm, 43.0mm, 75.6mm